

# ProLine Express Containment Switchfix

CONNECT AND PROTECT

## Part Number

UACSFPC2U850 2U 4.15 in. – 5.75 in. (105 mm – 146 mm) Black

UACSFPC1U116 1U 7.63 in. – 11.63 in. (194 mm – 295 mm) Black

UACSFPC1U850 1U 5.75 in. – 8.5 in. (146 mm – 216 mm) Black



## APPLICATIONS

The SwitchFix easily solves cooling problems associated with network switches without the need for additional energy usage. It allows your switches to benefit from cooler airflow and comply with Hot Aisle/Cold Aisle best practices.

Network switch equipment typically sits at the top and back portion of the server rack. This placement makes it difficult for cold air from the cold aisle to travel from the front of the rack to the intake side(s) of the Network Switch. The SwitchFix solves this problem by extending from the front of the rack in the cold aisle to the switch at the back of the rack. This allows cold air from the cold aisle to reach the network equipment for proper cooling.

The SwitchFix comes in a variety of sizes to meet the needs of many switches currently used in today's data centers. Each unit adjusts in depth to ensure an optimal flow of cooled air through to the installed switch. The SwitchFix easily accommodates front, rear, and side switch intakes and exhaust. The SwitchFix's passive airflow system channels air from the cold aisle to the switch, allowing cold air to pass through the switch intakes and prevents bypass and recirculated airflow. This prevents hot exhaust air from recycling through the installed equipment. This passive switch cooling solution can improve switch performance and life expectancy.

## FEATURES

- Channels cold air to the switch
- Prevents hot air recirculation
- Maintains cold aisle/hot aisle segregation
- Adjustable for a variety of depths
- Passive airflow circulation

## BENEFITS

- Maintains switch tenability and improves longevity of the switch
- Augments and improves upon airflow management best practices
- Supports over 203 switches in a passive application or 150 switches in an active\* application
- No additional power supply is required for the passive units
- Supports 1U and 2U switches

\*Active units are available upon request

## SPECIFICATIONS

Part Number	Description	Dimensions	Quantity per Carton	Shipping Weight
UACSFPC2U850	"Passive, Switch Rear Intake, 2U, Adjustable, Black"	4.15 in. – 5.75 in. (105 mm – 146 mm)	1	12 lbs.
UACSFPC1U116	"Passive, Switch Rear Intake, 1U, Adjustable, Black"	7.63 in. – 11.63 in. (194 mm – 295 mm)	1	9 lbs.
UACSFPC1U850	"Passive, Switch Rear Intake, 1U, Adjustable, Black"	5.75 in. – 8.5 in. (146 mm – 216 mm)	1	9 lbs.

### AIRFLOW

Passive (switch generated)

### SWITCH INTAKE

Supports switches with rear to front air intakes

### MATERIALS

- 18 Gauge Galvanized Steel
- RoHS Compliant
- Black Powder Coated Finish

### North America

#### All locations

Tel +1.763.422.2661

### Europe

#### Straubenhardt, Germany

Tel +49.7082.794.0

#### Betschdorf, France

Tel +33.388.90.64.90

#### Warsaw, Poland

Tel +48.22.209.98.35

#### Assago, Italy

Tel +39.02.5776151.224

### Middle East & India

#### Dubai, United Arab Emirates

Tel +971 4 823 8666

#### Bangalore, India

Tel +91.80.6715.8900

#### Istanbul, Turkey

Tel +90.216.250.7374

### Asia

#### Shanghai, P.R. China

Tel +86.21.2412.6943

#### Qingdao, P.R. China

Tel +86.523.8771.6101

#### Singapore

Tel +65.6768.5800

#### Shin-Yokohama, Japan

Tel +81.45.476.0271



Our powerful portfolio of brands:

**CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER**